



订购码 Ordering Code

A	C	4010	-	04	D
系列 Series	功能代号 Function Code	规格代号 Specification Code		接管口径 Port Size	排水方式 Drain Type
A系列 Series	二联件 F.R.L Combination	1010 2010 3010 4010 5010		M5: M5 × 0.8 02: G1/4" 04: G1/2" 10: G1"	空白: 差压排水 D: 自动排水 Blank: Differential Drain D: Automatic Drain

气源处理件
Air
Treatment
Units

规格 Specification

型号 Model		AC1010 -M5	AC2010 -01	AC2010 -02	AC3010 -02	AC3010 -03	AC4010 -03	AC4010 -04	AC4010 -06	AC5010 -06	AC5010 -10
额定流量/Rated Flow		90	500	500	1700	1700	3 000	3000	3000	4000	4000
接管口径/Port Size		M5	G1/8"	G1/4"	G1/4"	G3/8"	G3/8"	G1/2"	G3/4"	G3/4"	G1"
过滤精度/Filter Precision		25 μm									
最高使用压力 Highest Working Pressure		1.0MPa									
保证耐压力 Ensured Pressure Resistance		1.5MPa									
使用温度范围 Operating Temperature Range		5~60℃									
调节压力范围 Range of Adjustable Pressure		0.05~ 0.7MPa	0.05~0.85MPa								
建议用油 Recommended Oil Use		ISO VG 32									
容器材料/Container Material		聚碳酸酯 Polycarbonate									
防护罩/Protective Cover		无 Not Available			有 Available						
放水器功能/Drain Function		差压放水 Differential Drain	差压放水、自动放水 Differential Drain, Automatic Drain								
阀型/Valve Type		带溢流型 With Overflow									
构成元件 Composing Elements	过滤调压阀 Filter & Regulator	AW1000-M5	AW2000-01	AW2000-02	AW3000-02	AW3000-03	AW4000-03	AW4000-04	AW4000-06	AW5000-06	AW5000-10
	油雾器 Lubricator	AL1000-M5	AL2000-01	AL2000-02	AL3000-02	AL3000-03	AL4000-03	AL4000-04	AL4000-06	AL5000-06	AL5000-10