



订购码 Ordering Code

BC
型号 Model
AC: 小型 Small Size
BC: 中型 Middle Size

3000
接管口径 Port Size
1500: G1/8"
3000: G3/8"
2000: G1/4"
4000: G1/2"

D
排水方式 Drian Type
空白: 差压排水
D: 自动排水
D: Automatic Drain

气源处理件
Air
Treatment
Units

规格 Specification

型号 Model		AC1500	AC2000	BC2000	BC3000	BC4000
使用流体/Operating Fluid		空气 Air				
接管口径/Port Size		G1/8"	G1/4"	G1/4"	G3/8"	G1/2"
滤心粗度/Filtering Element Roughness		40 μ				
调节压力范围/Range of Adjustable Pressure		0.05~0.85MPa				
最大可调压力/Max. Adjustable Pressure		0.95MPa				
保证耐压/Ensured Pressure Resistance		1.5MPa				
使用温度范围/Operating Temp. Range		5~60℃				
滤水杯容量/Capacity of Filter Cup		15 cc		60 cc		
给油杯容量/Capacity of Oil Feed Cup		25 cc		90 cc		
建议润滑用油/Suggested Lube		ISO VG 32 或 同级用油		ISO VG 32 or Same Grade Oil		
重量/Weight		0.7 KG		0.9 KG		
材质 Material	本体/Body	铝合金压铸成型		Aluminum Die-casting Forming		
	容杯/Container Cup	PE				
	保护杯罩/Protective Cup Cover	—		铁 Iron		
构成元件 Composing Elements	过滤器/Filter	AF1500	AF2000	BF2000	BF3000	BF4000
	调压阀/Regulator	AR1500	AR2000	BR2000	BR3000	BR4000
	油雾器/Lubricator	AL1500	AL2000	BL2000	BL3000	BL4000

外形尺寸 Overall Dimension

