



- ▶ SUS316 不锈钢材质、耐高压、耐腐蚀、耐酸碱。
- ▶ 适用户外及有酸碱环境（不排气型）。
- ▶ 适用半导体工业。
- ▶ 流量大并有效快速排除水及微粒。
- ▶ 压力调整敏感精准。
- ▶ 轻量化，小型化，减少安装空间。
- ▶ 耐高压
- ▶ For high pressure use; corrosion and chemical resistance.
- ▶ Good performance for outdoor facility.
- ▶ Suitable for semi-conductor industry.
- ▶ Large flow rate and effectively removes water and particle.
- ▶ Accurate and sensitive pressure setting.
- ▶ Light weight; compact size for space saving.
- ▶ High pressure resistant.

订购码 / Ordering Code

DR		-	200	-	02	N	C
系列 /Series							
DR	过滤 + 调压 /Filter+Regulator						
阀体尺寸 /Body size							
200							
400							
600							
接管口径 /Joint pipe bore							
02	1/4						
03	3/8						
04	1/2						
06	3/4						
10	1"						
配管口螺牙 /Thread							
空白 /Blank:	G						
N:	NPT						
R:	RC						
工作温度 /Operating temperature							
空白 /Blank:	-10~80℃						
C:	-40℃						

规格表 / Specifications

型号 / Model	DR-200/400/600
配管尺寸 / Port size	1/4 3/8 1/2 3/4 1"
使用流体 / Fluid	压缩空气 / Compressed air
调压结构 / Regulator construction	活塞式 / Piston
本体材质 / Body material	不锈钢 SUS316 / Stainless Steel SUS316
压力表材质 / Pressure gauge material	外壳不锈钢 SUS304、牙口不锈钢 SUS316、/Case:Stainless steel SUS304, Thread:Stainless steel SUS316
操作压力 / Operating pressure range	0~20kgf/cm ²
最大进气压 / Proof pressure	30kgf/cm ²
最大流量 / Max. flow rate / 1/min (ANR)	1850 1/min
环境温度 / Ambient temperature	-10℃~70℃
净重 / Net weight	1200g
附属配件 / Accessories (Option)	压力表 (0~10kg)、塞头、固定架组 / Pressure gauge, Mounting bracket, Plug, Screw x 2
选配 / Match	压力表 (0~20kg)