



订购码 Ordering Code

2V	025	-	08	-	AC220V
规格代码 Model	流量孔径 Aperture of Flow Rate		接管口径 Port Size		标准电压 Standard Voltage
2V: 二位二通电磁阀 2V: 2/2 Way Solenoid Valve	025: 2.5mm		06: 1/8" 08: 1/4"		DC12V DC24V AC24V 50/60Hz AC36V 50/60Hz AC110V 50/60Hz AC220V 50/60Hz AC380V 50/60Hz

规格 Specification

型号 Model	2V025-06	2V025-08
工作介质/Working Medium	空气、水、油 Air, Water, Oil	
动作方式/Motion Pattern	直动式 Direct Drive Type	
型式/Type	常闭型/Normal Close Type	
流量孔径/Aperture of Flow Rate	2.5mm	
CV值/CV Value	0.23	
接管口径/Port Size	1/8"	1/4"
使用流体粘度度/Operation Fluid Viscosity	20 CST以下(below)	
使用压力/Working-pressure	空气、水、油 Air,Water,Oil: 0.05~0.7MPa	
最大耐压力/Max. Pressure Resistance	1.6MPa	
工作温度范围/Operating Temperature Range	-10~80℃	
使用电压范围/Voltage Range	± 10%	
保护等级/Protect Class	IP65	
耗电量/Power Consumption	AC: 6.5VA DC: 6.5W	
绝缘性/Insulation	F级 (Class)	
本体材质/Material of Body	铝或铜(镀镍处理) Aluminum or Brass	
油封材质/Material of Oil Seal	NBR 或(or) VITON	
最短励磁时间/Shortest Excitation Time	0.05秒 second	

外形尺寸 Overall Dimension

