



订购码 Ordering Code

HV	400	-	02	B	K	34	-	R ₈	L8
规格代码 Model	系列号 Series NO.		接管口径 Port Size	接管形式 Joint Pipe Type	规格代码 Model	位通数 Position and Way NO.		形式代号 Type Code	接管口径 Port Size
手转阀 Hand-switching			02: G1/4" 03: G3/8" 04: G1/2"	空白: 管接式 B: 板接式 Blank: Pipe Connection Type B: Plate Connection Type	手转阀 Hand-switching	24: 二位四通 34: 三位四通 24: 4/2 Way 34: 4/3 Way		R ₈ : 手转阀 R ₈ : Hand-switching Valve	L6: G1/8" L8: G1/4"

规格 Specification

型号 Model	HV400-02	HV400-03	HV400-04	K34R ₈ -L6	K34R ₈ -L8
工作介质/Working Medium	经40微米过滤的空气 40 Micron Filtered Air				
有效截面积/Effective Sectional Area	30mm ² (CV=1.68)			18mm ² (CV=1.00)	
接口口径/Port Size	G1/4"	G3/8"	G1/2"	G1/8"	G1/4"
使用压力范围/Working-pressure Range	0~0.8MPa				
使用温度范围/Operating Temperature	0~60℃				

* 公司可提供密封结构形式为橡胶软密封和陶瓷硬密封的手转阀。

* Company can offer Hand-switching Valve with soft rubber seals and hard pottery seals as the seal structure form.

外形尺寸 Overall Dimension

