

DSM 全不锈钢 NAMUR 电磁换向阀

DSM Series NAMUR Stainless steel solenoid valve

DGE



- ▶ 本产品为全不锈钢产品（不锈钢包含阀体，阀杆，手动按钮，先导头，先导座，M5*27 螺丝）
- ▶ 依据 NAMUR 国际标准，适用于双作用执行机构
- ▶ 自由交叉式切换
- ▶ 带不锈钢手动开关装置
- ▶ 适用于恶劣的环境中
- ▶ 适用于高温和抗腐蚀，适用酸碱及腐蚀介质。
- ▶ 密封材质为氟橡胶
- ▶ 可配合防爆线圈使用
- ▶ Complete Stainless steel material (Main body,Spool,Armature tube, Manual override,M5*27)
- ▶ NAMUR Standard, For double operated actuators
- ▶ Manual override with and Without detent
- ▶ Compact design with large flow rate
- ▶ Suitable for Critical environment. Low and high temperature.Dirty and pollution condition
- ▶ Corrosion resistant. High temperature resistance.
- ▶ Seal material : VITON
- ▶ All valves available with ex protected coils (ATEX and Other international approvals)

DSM 系列订购码 / SSM Series ordering

系列 / Series	SSM	不锈钢电磁阀 / Stainless steel solenoid valve
N	N	3/2 和 5/2 可变换 / 3/2 and 5/2 alteradle volatile variable
阀位数 / Number of positions	5	二位五通 / Two-position Five-way
	3	二位三通 / Two-position Three-way
阀体尺寸 / Body size	2	2 系列阀体 / 2 Series valve body
	3	3 系列阀体 / 3 Series valve body
	5	5 系列阀体 / 5 Series valve body
线圈及位数 / Coil and places	1	单电控 / Single-head
	2	双电控 / Double-head
接口 / Joint pipe bore	06	1/8
	08	1/4
	10	3/8
	15	1/2
线圈 / Solenoid coil	空白 / Blank	IP65(带接线盒 / With connector)
	Ex	防爆线圈 / Ex protected coils
工作温度 / Operating temperature	空白 / Blank	-20~80℃
	C1	-40~60℃
电磁铁电压 / Solenoid voltage	A	220V AC
	C	110V AC
	E	24V DC
	F	12V DC
配管口螺纹 / Thread	空白 / Blank	G
	N	NPT
	R	RC

型号 /Model	介质 Medium	公称通径 Orifice size(mm)	接管螺纹 Port connection(G)	工作压力 Operating pressure	工作温度 Operating temperature	介质温度 Medium temperature	流量 Flow(L/min)	换向时间 Switching time	不带线圈重量 Weight without solenoid(kg)
DSM521-08	气体 Air,Gas	5	1/4	0.2 ~ 0.8(MPa)	-20℃ ~ 180℃	-10℃ ~ 120℃	1200	35(ms)	0.35
DSM522-08		8							0.30
DSM531-15		12							0.66
DSM532-08		5					0.60		
DSM551-15		8	1/2				2400		1.12
DSM552-15		12							1.05
DSMN531-08		8							1700
DSMN532-08		8	1/4				1700		

▶ 别的电压可另行订制 / Several standard voltage grades are optional.

