

DSM 全不锈钢 NAMUR 电磁换向阀

DSM Series NAMUR Stainless steel solenoid valve

DGE



- ▶ 本产品为全不锈钢产品（不锈钢包含阀体，阀杆，手动按钮，先导头，先导座，M5*27 螺丝）
- ▶ 依据 NAMUR 国际标准，适用于双作用执行机构
- ▶ 自由交叉式切换
- ▶ 带不锈钢手动开关装置
- ▶ 适用于恶劣的环境中
- ▶ 适用于高温和抗腐蚀，适用酸碱及腐蚀介质。
- ▶ 密封材质为氟橡胶
- ▶ 可配合防爆线圈使用
- ▶ Complete Stainless steel material (Main body,Spool,Armature tube, Manual override,M5*27)
- ▶ NAMUR Standard, For double operated actuators
- ▶ Manual override with and Without detent
- ▶ Compact design with large flow rate
- ▶ Suitable for Critical environment. Low and high temperature.Dirty and pollution condition
- ▶ Corrosion resistant. High temperature resistance.
- ▶ Seal material : VITON
- ▶ All valves available with ex protected coils (ATEX and Other international approvals)

DSM 系列订购码 / SSM Series ordering

系列 / Series	DSM	5	3	1	-	08	E	Ex
DSM 不锈钢电磁阀 / Stainless steel solenoid valve								
N								
N 3/2 和 5/2 可变换 / 3/2 and 5/2 alteradle volatile variable								
阀位数 / Number of positions								
5 二位五通 / Two-position Five-way								
3 二位三通 / Two-position Three-way								
阀体尺寸 / Body size								
2 2 系列阀体 / 2 Series valve body								
3 3 系列阀体 / 3 Series valve body								
5 5 系列阀体 / 5 Series valve body								
线圈及位数 / Coil and places								
1 单电控 / Single-head								
2 双电控 / Double-head								
接口 / Joint pipe bore								
06 1/8								
08 1/4								
10 3/8								
15 1/2								
线圈 / Solenoid coil								
空白 / Blank IP65(带接线盒 / With connector)								
Ex 防爆线圈 / Ex protected coils								
工作温度 / Operating temperature								
空白 / Blank -20~80℃								
C1 -40~60℃								
电磁铁电压 / Solenoid voltage								
A 220V AC								
C 110V AC								
E 24V DC								
F 12V DC								
配管口螺牙 / Thread								
空白 / Blank G								
N NPT								
R RC								

型号 /Model	介质 Medium	公称通径 Orifice size(mm)	接管螺纹 Port connection(G)	工作压力 Operating pressure	工作温度 Operating temperature	介质温度 Medium temperature	流量 Flow(L/min)	换向时间 Switching time	不带线圈重量 Weight without solenoid(kg)
DSM521-08	气体 Air,Gas	5	1/4	0.2 ~ 0.8(MPa)	-20℃ ~ 180℃	-10℃ ~ 120℃	1200	35(ms)	0.35
DSM522-08		8							0.30
DSM531-15		12							0.66
DSM532-08		5					1700		0.60
DSM551-15		8	1/2				2400		1.12
DSM552-15		12							1.05
DSMN531-08		8	1/4				1700		
DSMN532-08		8							1700

▶ 别的电压可另行订制 / Several standard voltage grades are optional.

